



DATA DIMENSIONS AND FEATURES ARE INDICATIVE AND NOT BINDING.

Max. working height, ft	82'
Max. side reach, ft	40'
Max. basket load, lbs	440 lbs
Rotation	± 400°
Basket size, ft (w x l x h)	4'1"x2'10"x3'8"
Basket Rotation	± 41°
Battery	24V/200Ah/5h
Charger	24V/30 A
Transport length, ft	26'11"
Transport height, ft	6'9"
Transport width, ft	5'5"
Outrigger Spread, ft	13'7"
Total weight, lbs	6732 lbs
Deployment ability	3.1° (5.4%)
110V outlet in basket, Max. 10A	Standard
Diesel engine, EBD model	Kubota D722 18.8 hp
Gasoline engine, EBP model	Honda GX200 6.5 hp
Manual Emergency Lowering	Standard

*ED Diesel only version also available
EP Gasoline only version also available*

ANSI compliant.

OPTIONS

- » Self Propulsion
- » Outrigger & Self Propulsion Controls in Basket
- » Fiberglass basket insulated to 1000V
- » Spotlight in the basket
- » Heavy duty nose wheel (standard with self propulsion)
- » Flashing beacon lights on boom and stabilizers (5)
- » Transformer 24V/100A, allows continuous battery operation
- » Custom Colors
- » Intercom
- » Increased battery capacity, 400Ah EB model only