



Outrigger Spread Diagram see page 26.
DATA DIMENSIONS AND FEATURES ARE INDICATIVE AND NOT BINDING.

Max. working height, ft	90'
Max. side reach, ft	52'
Rotation	551 lbs at full height
Max. basket load	± 400°
Basket size, ft (w x l x h)	4'1"x2'10"x3'8"
Basket Rotation	± 41°
Moveable Jib Range	90°
Battery	24V/200Ah/5h
Charger	24V/30 A
Diesel engine, Kubota D722	14 kW/18.8 hp
Transport length, ft	24'7"
Transport height, ft	7'3"
Transport width, ft	3'8" - 4'11"
Outrigger Spread-Wide, ft	17'5"/15'0" (max/min)
Outrigger Spread-Narrow, ft	10'6"/9'4" (max/min)
Total weight, lbs	10,989 lbs
Gradeability - up hill	19.3° (35%)
Gradeability - cross hill	14° (25%)
Deployment ability	21.8° (40%)
Crawler track length, ft	6'3"
110V outlet in basket, Max. 10A	Standard
Variable Width Undercarriage, 3'8" - 4'11"	Standard
Manual Emergency Lowering	Standard

Battery only (400 Ah) version available

ANSI compliant.

OPTIONS

- >> Fiberglass basket insulated to 1000V
- >> Spotlight in the basket
- >> Intercom
- >> Flashing beacon lights on boom and stabilizers (5)
- >> Radio Remote Control Drive
- >> Auto Leveling
- >> Custom Colors
- >> White Rubber Tracks
- >> 2nd Electric Drive Motor
- >> Increased battery capacity, 400Ah